











Type:

Job:

Page: 2 of 4




## Standard Features

<p><b>Mounting</b>          Consult factory for other mounting applications.</p>				
	Cat. No.:	<input type="checkbox"/> <b>FM</b> Flush Mount	<input type="checkbox"/> <b>PT</b> Post Tenon Mount	
	Pole Top Requirements	5" O.D. poles only.		2" Pipe-size Tenon (2 <sup>3</sup> / <sub>8</sub> " O.D. x 4" minimum length)
<p><b>Fixture</b>          Cat. No. designates <b>WTV</b> fixture and light distribution.           See the Kim Site/Roadway Optical Systems Catalog for detailed information on reflector design and application</p>	<p><b>Vertical Lamp</b></p>  <p>Light Distribution:</p>	 <p>Asymmetric</p> <p>Cat. No.: <input type="checkbox"/> <b>WTV3</b></p>	 <p>Symmetric Square</p> <p>Cat. No.: <input type="checkbox"/> <b>WTV5</b></p>	

Type:

Job:

Page: 3 of 4




## Standard Features

### Electrical Module

**PMH** = Pulse Start  
 Metal Halide

**HPS** = High Pressure  
 Sodium



Lamp Watts	Lamp Type	Line Volts
250	MH	277

Cat. Nos. for Electrical Modules available:

Pulse Start Metal Halide			
<input type="checkbox"/>	<b>175PMH120<sup>1</sup></b>	<input type="checkbox"/>	<b>250PMH120</b>
<input type="checkbox"/>	<b>175PMH208<sup>1</sup></b>	<input type="checkbox"/>	<b>250PMH208</b>
<input type="checkbox"/>	<b>175PMH240<sup>1</sup></b>	<input type="checkbox"/>	<b>250PMH240</b>
<input type="checkbox"/>	<b>175PMH277<sup>1</sup></b>	<input type="checkbox"/>	<b>250PMH277</b>
<input type="checkbox"/>	<b>175PMH347<sup>1</sup></b>	<input type="checkbox"/>	<b>250PMH347</b>
<input type="checkbox"/>	<b>175PMH480<sup>1</sup></b>	<input type="checkbox"/>	<b>250PMH480</b>
Lamp	ED-28 Clear	BT-28 or ED-28 Clear	
Socket	Mogul Base	Mogul Base	
ANSI Ballast Type	M-137, M-152	M-138, M-153	
High Pressure Sodium			
<input type="checkbox"/>	<b>150HPS120</b>	<input type="checkbox"/>	<b>250HPS120</b>
<input type="checkbox"/>	<b>150HPS208</b>	<input type="checkbox"/>	<b>250HPS208</b>
<input type="checkbox"/>	<b>150HPS240</b>	<input type="checkbox"/>	<b>250HPS240</b>
<input type="checkbox"/>	<b>150HPS277</b>	<input type="checkbox"/>	<b>250HPS277</b>
<input type="checkbox"/>	<b>150HPS347</b>	<input type="checkbox"/>	<b>250HPS347</b>
<input type="checkbox"/>	<b>150HPS480</b>	<input type="checkbox"/>	<b>250HPS480</b>
Lamp	ED-23½ Clear	ED-18 or ET-18 Clear	
Socket	Mogul Base	Mogul Base	
ANSI Ballast Type	S-55	S-50	

**NOTE:** For lamp/ballast information outside of the U.S.A. and Canada, please consult your local Kim representative.

<sup>1</sup>175W pulse rated lamps are for use in verticle lamp luminaires only.

**NOTE:** Due to the Energy Independence and Security Act (EISA) of 2007, Kim Lighting can no longer supply probe start metal halide ballasts with its luminaires, effective January 1, 2009. Contact Kim Lighting for availability of replacement ballasts for warranty service claims.

(Visit [www.aboutlightingcontrols.org](http://www.aboutlightingcontrols.org) or the Library of Congress website for more details).

### Finish

Super TGIC thermoset polyester powder coat paint applied over a titanated zirconium conversion coating.


Color: Black Dark Bronze Light Gray Stealth Gray™ Platinum Silver White Custom Color<sup>2</sup>  
 Cat. No.:  **BL**  **DB**  **LG**  **SG**  **PS**  **WH**  **CC**

<sup>2</sup>Custom colors subject to additional charges, minimum quantities and extended lead times. Consult representative. Custom color description: \_\_\_\_\_






Type:

Job:

Page: 4 of 4



## Optional Features

<p><b>Photocell</b> Cat. No. <b>(See right)</b> <input type="checkbox"/> No Option</p>	<p>Factory installed photocell inside housing with a fully gasketed sensor on the side wall.</p> <table border="0"> <tr> <td>Cat. No.</td> <td>Line Volts:</td> <td>Cat. No.</td> <td>Line Volts:</td> </tr> <tr> <td><input type="checkbox"/> <b>A-30</b></td> <td>120V</td> <td><input type="checkbox"/> <b>A-33</b></td> <td>277V</td> </tr> <tr> <td><input type="checkbox"/> <b>A-31</b></td> <td>208V</td> <td><input type="checkbox"/> <b>A-34</b></td> <td>480V</td> </tr> <tr> <td><input type="checkbox"/> <b>A-32</b></td> <td>240V</td> <td><input type="checkbox"/> <b>A-35</b></td> <td>347V</td> </tr> </table>	Cat. No.	Line Volts:	Cat. No.	Line Volts:	<input type="checkbox"/> <b>A-30</b>	120V	<input type="checkbox"/> <b>A-33</b>	277V	<input type="checkbox"/> <b>A-31</b>	208V	<input type="checkbox"/> <b>A-34</b>	480V	<input type="checkbox"/> <b>A-32</b>	240V	<input type="checkbox"/> <b>A-35</b>	347V	 <p>Photocell</p>
Cat. No.	Line Volts:	Cat. No.	Line Volts:															
<input type="checkbox"/> <b>A-30</b>	120V	<input type="checkbox"/> <b>A-33</b>	277V															
<input type="checkbox"/> <b>A-31</b>	208V	<input type="checkbox"/> <b>A-34</b>	480V															
<input type="checkbox"/> <b>A-32</b>	240V	<input type="checkbox"/> <b>A-35</b>	347V															
<p><b>Polycarbonate Lens</b> Cat. No. <input type="checkbox"/> <b>LS</b> <input type="checkbox"/> No Option</p>	<p>Clear, injection molded, UV stabilized polycarbonate replaces standard acrylic lens. <b>CAUTION:</b> Use only when vandalism is anticipated to be high. Useful life is limited by UV discoloration from sunlight and metal halide lamps.</p>	 <p>Polycarbonate Lens</p>																
<p><b>Houseside Shield</b> Cat. No. <input type="checkbox"/> <b>HS</b> <input type="checkbox"/> No Option</p>	<p>Available for Asymmetric reflector only. Clear anodized, stamped aluminum, bypass louvers on streetside; black anodized panel on houseside. Attaches to reflector. <b>NOTE:</b> Use with clear lamps only.</p>	 <p>Houseside Shield</p>																
<p><b>Glow Cap</b> Cat. No. <input type="checkbox"/> <b>GC</b> <input type="checkbox"/> No Option</p>	<p>Center cone cap in bright dip finish. Provides visual bright accent at pole cap, inside lens enclosure. <b>NOTE:</b> Not recommended for use with Houseside Shield.</p>	 <p>Glow Cap</p>																
<p><b>Accent Reveals</b> Cat. No. <b>(See right)</b> <input type="checkbox"/> No Option</p>	<p>Three aluminum bands riveted inside the housing reveals. Available in five standard Kim powder coat finishes: Black, Dark Bronze, Light Gray, Platinum Silver, or White. Custom colors are available.</p> <p>Color:    Black            Dark Bronze    Light Gray    Stealth Gray™    Platinum Silver    White            Custom Color<sup>1</sup></p> <p>Cat. No.: <input type="checkbox"/> <b>BL-REV</b>   <input type="checkbox"/> <b>DB-REV</b>   <input type="checkbox"/> <b>LG-REV</b>   <input type="checkbox"/> <b>SG-REV</b>   <input type="checkbox"/> <b>PS-REV</b>   <input type="checkbox"/> <b>WH-REV</b>   <input type="checkbox"/> <b>CC-REV</b></p> <p><sup>1</sup>Custom colors subject to additional charges, minimum quantities and extended lead times. Consult representative. Custom color description: _____</p>	 <p>Accent Reveals</p>																