

**Type:**

**Job:**

**Fixture Catalog number:**

**LLV205BL**

Fixture and Finish

**Mounting Options:**

**Stake Mount Only (Included)**

Ordered Separately from Fixture

**Approvals:**

**Date:**

**Page: 1 of 1**

## Specifications

**Housing and Shield:** Die-cast aluminum. No-tool twist-on shield provided with drain slot.

**Swivel:** Die-cast aluminum with locking teeth, 20mm threaded stem. Stainless steel screw.

**Stake:** Die-cast aluminum, included.

**Lens:** 3/16" thick flat tempered glass with silicone gasket.


**Socket:** GU5.3 socket for bipin lamp.

**Wire:** 10" No. 18 12 Volt wire with fork connectors.

**Lamp:** 20 watt MR16 flood (BAB) included.

**Finish:** Black (BL) powder coat paint only.

**Certification:** UL Listed to U.S. and Canadian safety standards for wet locations. Fixture manufacturer shall employ a quality program that is certified to meet the ISO 9001:2000 standard.



## ORDERING INFORMATION

**Fixture\***

**LLV205BL**

### Wattage / Lamp

**20W - 35W**

20 watt MR16 Bipin  
 Halogen included

**NOTE:** 20W BAB MR16 Lamp and Stake included with fixture.

## MOUNTING INFORMATION:

**Stake Mount Only** (included)

\*Remote transformer required.



Lighting, Inc.

